



TOTAL CABLE CLAMPING RANGE= Ø10.0-Ø18.0mm

Triple Seal :Ø10.0 - Ø12.0mm

Double Seal :Ø12.0 - Ø14.5mm

Single seal :Ø14.5 - Ø18.0mm

No/Nu.	Qty/Ad.	Part Name/Parça Adı	Material/Malzeme
8	1	Ø22x2.0mm O-RING	VMQ
7	1	3/4" Ex-e CORVUS FERRULE	Ms 58 Brass (nickel plated) or Stainless Steel
6	1	Ø20.2x1.6 CORVUS WIRE RING	SPRING STEEL
5	1	M26x1.0 Ex-e CORVUS CAP	Ms 58 Brass (nickel plated) or Stainless Steel
4	1	M25 Ex-db/eb OCTANS OUTER SEALING Ø18	CR, VMQ
3	1	M25 Ex-db/eb OCTANS INNER SEALING Ø14.5	CR, VMQ
2	1	M25 Ex-db/eb OCTANS INNER SEALING Ø12	CR, VMQ
1	1	M25x1.5 Ex-db/eb OCTANS BODY (M26x1.0) TL16	Ms 58 Brass (nickel plated) or Stainless Steel

Part List / Parça Listesi

Revision / Revizyon	No Nu.	Letter Harfi	Date Tarih	Realised By Gerçekleştiren	Required By İsteyen	Approved By Onaylayan
O-Ring ve contaların malzemeleri güncellendi.NBR kullanımı kaldırıldı.	01	-	03.09.2015	15-451	Y.CAN	O.ELÇİ

Drawing Number / Resim No	Reference Number / Ref. No	Bimed Code / Bimed Kodu	Customer Code / Müşteri Kodu	Date / Tarih	Signature / İmza	Material / Malzeme	Mass / Ağırlık	Nominal size ranges / Anma ölçü aralıkları	Value / Değer
		EBMC2M		03.04.2013		M25x1.5 Ex-e CORVUS RAKOR (M26x1.0) TL16 M25x1.5 Ex-e CORVUS GLAND (M26x1.0) TL16	108,386 g	0.5s...<3	±0,05
Designed by / Tasarlayan	Nursel ORAL			16.07.2013				3s...<6	±0,05
Drawn by / Çizen	Mustafa KOCAOĞLU							6s...<30	±0,10
Approved by / Onaylayan	Yılmaz ALBUKREK							30s...<120	±0,15
Scale / Ölçek	Form							120s...<400	±0,20
5/2	A3								

bimed